





# LUXEON 3030 HE Plus

# Industry leading efficacy, 3V 3030 package







#### Now With NightScape Technology

NightScape Technology enables white light with blue light content that is less than 2%.

#### **FEATURES AND BENEFITS**

Superior high efficacy at rated current enables outstanding lm/W at system level

Reliable package design from a proven product line affirms application long lifetime

Quadrant bin structure within 3 SDCM enables 2 SDCM by kitting

Industry standard package allows drop-in replacement for existing 3030 packages

Robust coating design for enhanced sulfurprotection capability (LUXEON 3030 HE Plus)  $^{\scriptsize{[1]}}$ 

[1] Refer to reliability datasheet for more details.

#### **PRIMARY APPLICATIONS**

Panel / Soft Lights
Spotlights
Linear
Troffers
Downlights
Wall Pack
Horticulture



# **Table of Contents**

General Product Information	
Product Test Conditions	
Part Number Nomenclature	
Lumen Maintenance	
Environmental Compliance	
Performance Characteristics	
Product Selection Guide	
Optical Characteristics	
Electrical and Thermal Characteristics	
Absolute Maximum Ratings	
Characteristics Curves	
Spectral Power Distribution Characteristics	
Light Output Characteristics	
Forward Current Characteristics	
Radiation Pattern Characteristics	
Product Bin and Labeling Definitions	
Decoding Product Bin Labeling	
Luminous Flux Bins	
Color Bin Definitions	
Forward Voltage Bins	
Mechanical Dimensions	
Reflow Soldering Guidelines	
JEDEC Moisture Sensitivity	
Solder Pad Design	
Packaging Information	
Pocket Tape Dimensions	
Reel Dimensions	
About Lumileds	21

#### **General Product Information**

#### **Product Test Conditions**

LUXEON 3030 HE and LUXEON 3030 HE Plus LEDs are tested and binned with a 20ms monopulse of 65mA at a junction temperature,  $T_{\nu}$  of 25°C.

#### Part Number Nomenclature

Part numbers for LUXEON 3030 HE and LUXEON 3030 HE Plus follow the convention below:

L 1 3 0 - A A A A B B 3 0 C C C C C

Where:

AAAA – designates nominal CCT and CRI (2780=2700K, 80CRI; 3090=3000K, 90CRI, etc., and NSC1=Nightscape)

B B - designates product code (HA=LUXEON 3030 HE Plus, HB=LUXEON 3030 HE)

C C C C C - designates options for product specification (000B1 = base part number of performance proliferation B1, 000C1 = base part number of performance proliferation C1. Besides, there would be custom part numbers that are derived from base part number for kitting purpose etc., and those would take the last five digits to differentiate from base part number. For examples, 000B4 = 3SDCM kitting by opposite bin of proliferation B1, 000B5 = pure 3SDCM of proliferation B1, 000B7 = 2SDCM by opposite bin kitting from four 3SDCM inner bins of proliferation B1)

Therefore, the following part number is used for a LUXEON 3030 HE Plus, 3000K 80CRI LED with pure 3SDCM of proliferation C1:

L 1 3 0 - 3 0 8 0 H A 3 0 0 0 0 C 5

#### Lumen Maintenance

Please contact your local Sales Representative or Lumileds Technical Solutions Manager for more information about the long-term performance of this product.

## **Environmental Compliance**

Lumileds LLC is committed to providing environmentally friendly products to the solid-state lighting market. LUXEON 3030 HE is compliant to the European Union directives on the restriction of hazardous substances in electronic equipment, namely the RoHS Directive 2011/65/EU including amendments 2015/863/EU & 2017/2102/EU and REACH Regulation (EC) 1907/2006. Lumileds LLC will not intentionally add the following restricted materials to its products: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE).

# **Performance Characteristics**

## **Product Selection Guide**

Table 1a. Product performance of LUXEON 3030 HE and LUXEON 3030 HE Plus at 65mA, T<sub>i</sub>= 25°C

			LUMINOUS F	LUX [2, 3] (lm)	TYPICAL LUMINOUS	
PART	NOMINAL CCT [1]	MINIMUM CRI <sup>[2, 3]</sup>	MINIMUM	TYPICAL	EFFICACY (lm/W)	PART NUMBER
				65mA		
•	3000K	70	32.7	35.5	195	L130-3070HB30000B
	3500K	70	34.0	37.0	203	L130-3570HB30000B
	4000K	70	34.5	37.5	206	L130-4070HB30000B
_	5000K	70	34.5	37.5	206	L130-5070HB30000B
	5700K	70	34.0	37.0	203	L130-5770HB30000B
	6500K	70	33.5	36.4	200	L130-6570HB30000B
	2700K	80	29.0	33.5	184	L130-2780HB30000B
	3000K	80	29.5	34.0	187	L130-3080HB30000B
	3500K	80	30.0	35.0	192	L130-3580HB30000B
	4000K	80	32.0	36.5	201	L130-4080HB30000B
LUXEON 3030 HE -	5000K	80	31.5	36.0	198	L130-5080HB30000B
_	5700K	80	31.5	36.0	198	L130-5780HB30000B
_	6500K	80	31.0	35.5	195	L130-6580HB30000B
_	2700K	90	24.5	28.0	154	L130-2790HB30000B
_	3000K	90	25.0	28.5	157	L130-3090HB30000B
_	3500K	90	26.0	29.5	162	L130-3590HB30000B
_	4000K	90	27.5	30.5	168	L130-4090HB30000B
_	5000K	90	27.0	30.0	165	L130-5090HB30000B
_	5700K	90	27.0	30.0	165	L130-5790HB30000B
_	6500K	90	27.0	30.0	165	L130-6590HB30000B
	2200K	70	29.5	32.0	182	L130-2270HA30000B
_	3000K	70	34.0	37.0	210	L130-3070HA30000B
_	3500K	70	35.0	38.0	216	L130-3570HA30000B
_	4000K	70	36.0	39.0	221	L130-4070HA30000B
_	5000K	70	36.0	39.0	221	L130-5070HA30000B
_	5700K	70	35.0	38.0	216	L130-5770HA30000B
_	6500K	70	34.5	37.5	213	L130-6570HA30000B
_	2700K	80	30.0	33.5	190	L130-2780HA30000B
_	3000K	80	32.0	35.0	199	L130-3080HA30000B
_	3500K	80	33.0	36.0	204	L130-3580HA30000B
LUXEON 3030 — HE Plus —	4000K	80	34.0	37.0	210	L130-4080HA30000B
TIL FIUS _	5000K	80	34.0	37.0	210	L130-5080HA30000B
_	5700K	80	33.5	36.5	207	L130-5780HA30000B
_	6500K	80	33.0	36.0	204	L130-6580HA30000B
_	2700K	90	26.0	28.5	162	L130-2790HA30000B
_	3000K	90	27.0	29.5	167	L130-3090HA30000B
_	3500K	90	27.5	30.5	173	L130-3590HA30000B
_	4000K	90	28.5	31.5	179	L130-4090HA30000B
_	5000K	90	28.5	31.5	179	L130-5090HA30000B
_	5700K	90	28.5	31.5	179	L130-5790HA30000B
_	6500K	90	28.0	31.0	176	L130-6590HA30000B

Table 1a continued on next page:

1. Correlated color temperature is hot targeted at T<sub>j</sub>=85°C.

2. Luminous flux and CRI are specified at T<sub>j</sub>=25°C. Typical CRI is approximately 2 points higher than the minimum CRI specified, but this is not guaranteed.

3. Lumileds maintains a tolerance of ±2 on CRI and ±7.5% on luminous flux measurements.

Table 1a. Product performance of LUXEON 3030 HE and LUXEON 3030 HE Plus at 65mA, T.= 25°C, Continued.

	NIGRAINIAI		LUMINOUS F	LUX [2, 3] (lm)	TYPICAL LUMINOUS	PART NUMBER	
PART	NOMINAL CCT [1]	MINIMUM CRI [2, 3]	MINIMUM	TYPICAL	EFFICACY (lm/W)		
				65mA			
_	1850K <sup>[4]</sup>	50	29.5	32.2	183	L130-NSC1HA30000C1	
	2200K	70	29.5	33.1	188	L130-2270HA30000C1	
	3000K	70	34.0	37.7	215	L130-3070HA30000C1	
	3500K	70	35.0	38.7	221	L130-3570HA30000C1	
	4000K	70	36.0	39.4	224	L130-4070HA30000C1	
	5000K	70	36.0	39.4	224	L130-5070HA30000C1	
	5700K	70	35.0	38.5	219	L130-5770HA30000C1	
	6500K	70	34.5	38.0	216	L130-6570HA30000C1	
	2700K	80	30.0	33.8	193	L130-2780HA30000C1	
	3000K	80	32.0	35.2	201	L130-3080HA30000C1	
LUXEON 3030	3500K	80	33.0	36.6	209	L130-3580HA30000C1	
HE Plus	4000K	80	34.0	37.6	214	L130-4080HA30000C1	
	5000K	80	34.0	37.6	214	L130-5080HA30000C1	
	5700K	80	33.5	37.0	211	L130-5780HA30000C1	
	6500K	80	33.0	36.6	209	L130-6580HA30000C1	
	2700K	90	26.0	28.8	164	L130-2790HA30000C1	
	3000K	90	27.0	30.0	171	L130-3090HA30000C1	
	3500K	90	27.5	30.5	174	L130-3590HA30000C1	
-	4000K	90	28.5	32.1	183	L130-4090HA30000C1	
-	5000K	90	28.5	32.1	183	L130-5090HA30000C1	
-	5700K	90	28.5	32.1	183	L130-5790HA30000C1	
	6500K	90	28.0	31.3	178	L130-6590HA30000C1	

#### Notes for Table 1a:

- 1. Correlated color temperature is hot targeted at T<sub>i</sub>=85°C.

  2. Luminous flux and CRI are specified at T<sub>i</sub>=25°C. Typical CRI is approximately 2 points higher than the minimum CRI specified, but this is not guaranteed.

  3. Lumileds maintains a tolerance of ±2 on CRI and ±7.5% on luminous flux measurements.

Table 1b. Percent Blue for LUXEON 3030 HE Plus with NightScape Technology at test current, T,=25°C

PART NUMBER	BLUE CO	NTENT [1]
PART NOWIDER	TYPICAL	MAXIMUM
L130-NSC1HA30000C1	1%	2%

Notes for Table 1b:

## **Optical Characteristics**

Table 2. Optical characteristics for LUXEON 3030 HE and LUXEON 3030 HE Plus at 65mA, T<sub>i</sub>= 25°C

PART NUMBER	TYPICAL TOTAL INCLUDED ANGLE [1]	TYPICAL VIEWING ANGLE [2]
L130-xxxxHx30000x1	160°	110°

Notes for Table 2:

- Total angle at which 90% of total luminous flux is captured.
- 2. Viewing angle is the off axis angle from the LED centerline where the luminous intensity is ½ of the peak value.

<sup>4.</sup> With Nightscape technology inside.

<sup>1.</sup> Blue content is defined as the radiometric flux emitted between 400nm and 500nm divided by the total radiometric power.

#### **Electrical and Thermal Characteristics**

Table 3. Electrical and thermal characteristics for LUXEON 3030 HE and LUXEON 3030 HE Plus at 65mA, T,= 25°C

PART NUMBER	FORW	ARD VOLTAGI	5 P		TYPICAL THERMAL	
PART NUMBER	MINIMUM	TYPICAL	MAXIMUM	VOLTAGE [2] (mV/°C)	RESISTANCE—JUNCTION TO SOLDER PAD (°C/W)	
L130-xxxHA30000x1	2.66	2.70	2.76	-1.0 to -2.0	10.0	
L130-xxxxHB30000B1	2.75	2.80	2.85	-1.0 to -2.0	23.0	

#### Notes for Table 3:

# **Absolute Maximum Ratings**

Table 4. Absolute maximum ratings for LUXEON 3030 HE and LUXEON 3030 HE Plus

PARAMETER	MAXIMUM PERFORMANCE
DC Forward Current <sup>[1]</sup>	240mA/480mA
Peak Pulsed Forward Current [2]	350mA/700mA
ESD Sensitivity (ANSI/ESDA/JEDEC JS-001-2012)	Class 2
LED Junction Temperature (DC & Pulse)	125°C
Operating Case Temperature	-40°C to 105°C
LED Storage Temperature	-40°C to 105°C
Soldering Temperature	JEDEC 020D 260°C
Allowable Reflow Cycles	3
Reverse Voltage (V <sub>reverse</sub> ) <sup>[3]</sup>	-5V

#### Notes for Table 4:

<sup>1.</sup> Lumileds maintains a tolerance of ±0.1V on forward voltage measurements. 2. Measured between 25°C and 85°C.

<sup>1.</sup> Residual periodic variations due to power conversion from alternating current (AC) to direct current (DC), also called "ripple", are acceptable if the following conditions are met:

The frequency of the ripple current is 100Hz or higher

The average current for each cycle does not exceed the maximum allowable DC forward current

The maximum amplitude of the ripple does not exceed 25% of the maximum allowable DC forward current

Pulse operation with the maximum peak pulse forward current is acceptable if the pulse on time is ≤5ms per cycle and the duty cycle is ≤50%

At a maximum reverse current of 10μA. LUXEON 3030 HE and LUXEON 3030 HE Plus LEDs are not designed to be driven in reverse bias.

## **Characteristics Curves**

# **Spectral Power Distribution Characteristics**




Figure 1a. Typical normalized power vs. wavelength for L130-xx80Hx30000x1 at 65mA, T<sub>i</sub>=25°C




Figure 1b. Typical normalized power vs. wavelength for L130-xx70Hx30000x1 at 65mA, T<sub>i</sub>=25°C




Figure 1c. Typical normalized power vs. wavelength for L130-xx90Hx30000x1 at 65mA,  $T_j$ =25°C




Figure 1d. Typical normalized power vs. wavelength for L130-NSC1HA30000C1 at 65mA,  $T_i$ =25°C

# **Light Output Characteristics**






Figure 2. Typical normalized light output vs. junction temperature for L130-xxxxHx30000x1 at 65mA



ESTIMATED TYPICAL RATIO COMPARED TO FLUX AT RATED CONDITION 65mA, $T_j$ =25°C.					
60mA	65mA	120mA	150mA	480mA	
93%	100%	180%	222%	641%	

Figure 3. Typical normalized light output vs. forward current for L130-xxxxHA30000x1 at  $T_i$ =25°C



ESTIMATED TYPICAL RATIO COMPARED TO FLUX AT RATED CONDITION 65mA, $T_j$ =25°C.						
60mA	65mA	120mA	150mA	480mA		
93%	100%	177%	216%	325%		

Figure 4. Typical normalized light output vs. forward current for L130-xxxxHB30000x1 at T<sub>i</sub>=25°C

## **Forward Current Characteristics**




Figure 5. Typical forward current vs. forward voltage for L130-xxxxHx30000x1 at T<sub>i</sub>=25°C

## **Radiation Pattern Characteristics**




Figure 6. Typical radiation pattern for L130-xxxxHx30000x1 at 65mA, T<sub>i</sub>=25°C




Figure 7. Typical polar radiation pattern for L130-xxxxHx30000x1 at 65mA, T<sub>i</sub>=25°C

# **Product Bin and Labeling Definitions**

## **Decoding Product Bin Labeling**

In the manufacturing of semiconductor products, there are variations in performance around the average values given in the technical datasheet. For this reason, Lumileds bins LED components for luminous flux or radiometric power, color point, peak or dominant wavelength and forward voltage.

LUXEON 3030 HE and LUXEON 3030 HE Plus LEDs are labeled using a 4- or 5-digit alphanumeric CAT code following the format below:

#### ABCD or AxBCD

A - designates luminous flux bin (example: F=35.5 to 37.0 lm, G=37.0 to 38.5 lm)

x – designates Lumileds internal code

B C - designates color bin (example: 5E, 5H, 5F, 5G for 4000K parts)

designates forward voltage bin (K=2.66 to 2.76V)

Therefore, a LUXEON 3030 HE and LUXEON 3030 HE Plus with a lumen range of 35.5 to 37.0 lm, color bin of 5E, and a forward voltage range of 2.66 to 2.76V has the following CAT code:

#### F 5 E K

#### **Luminous Flux Bins**

Table 5 lists the standard luminous flux bins for LUXEON 3030 HE emitters. Although several bins are outlined, product availability in a particular bin varies by production run and by product performance. Not all bins are available in all CCTs.

Table 5. Luminous flux bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus at 65mA, T = 25°C

	LUMINOUS FLUX <sup>[1]</sup> (lm)				
BIN	MINIMUM	MAXIMUM			
Y	25.0	26.5			
Z	26.5	28.0			
A	28.0	29.5			
В	29.5	31.0			
С	31.0	32.5			
D	32.5	34.0			
Е	34.0	35.5			
F	35.5	37.0			
G	37.0	38.5			
Н	38.5	40.0			
J	40.0	41.5			

Notes for Table 5:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 7.5\%$  on luminous flux measurements.

## Color Bin Definitions




Figure 8. 3- and 5-step MacAdam ellipse illustration for Tables 6a-6g




Figure 9a. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 2700K, at 65mA, T<sub>i</sub>=25°C

Table 6a. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 2700K, at 65mA, T<sub>i</sub>=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
2700K	Single 3-Step MacAdam ellipse	(0.4578, 0.4101)	0.00810	0.00420	53.70°
2700K	Single 5-Step MacAdam ellipse	(0.4578, 0.4101)	0.01350	0.00700	53.70°

Notes for Table 6a:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.




Figure 9b. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 3000K, at 65mA, T<sub>i</sub>=25°C

Table 6b. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 3000K, at 65mA, T<sub>i</sub>=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
3000K	Single 3-Step MacAdam ellipse	(0.4338, 0.4030)	0.00834	0.00408	53.22°
3000K	Single 5-Step MacAdam ellipse	(0.4338, 0.4030)	0.01390	0.00680	53.22°

Notes for Table 6b:

1. Lumileds maintains a tolerance of ±0.007 on x and y color coordinates in the CIE 1931 color space.




Figure 9c. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 3500K, at 65mA, T<sub>i</sub>=25°C

Table 6c. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 3500K, at 65mA, T,=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
3500K	Single 3-Step MacAdam ellipse	(0.4073, 0.3917)	0.00927	0.00414	54.00°
3500K	Single 5-Step MacAdam ellipse	(0.4073, 0.3917)	0.01545	0.00690	54.00°

Notes for Table 6c:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.




Figure 9d. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 4000K, at 65mA, T<sub>i</sub>=25°C

Table 6d. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 4000K, at 65mA, T<sub>i</sub>=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, O
4000K	Single 3-Step MacAdam ellipse	(0.3818, 0.3797)	0.00939	0.00402	53.72°
4000K	Single 5-Step MacAdam ellipse	(0.3818, 0.3797)	0.01565	0.00670	53.72°

Notes for Table 6d:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.




Figure 9e. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 5000K, at 65mA, T,=25°C

Table 6e. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 5000K,at 65mA, T,=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
5000K	Single 3-Step MacAdam ellipse	(0.3447, 0.3553)	0.00822	0.00354	59.62°
5000K	Single 5-Step MacAdam ellipse	(0.3447, 0.3553)	0.01370	0.00590	59.62°

Notes for Table 6e:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.




Figure 9f. 1/8<sup>th</sup> color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 5700K, at 65mA, T<sub>i</sub>=25°C

Table 6f. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 5700K, at 65mA, T<sub>i</sub>=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
5700K	Single 3-Step MacAdam ellipse	(0.3287, 0.3417)	0.00746	0.00320	59.09°
5700K	Single 5-Step MacAdam ellipse	(0.3287, 0.3417)	0.01243	0.00533	59.09°

Notes for Table 6f:

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.




Figure 9g. 1/8th color bin structure for LUXEON 3030 HE and LUXEON 3030 HE Plus 6500K, at 65mA, T<sub>i</sub>=25°C

Table 6g. 3- and 5-step MacAdam ellipse color bin definitions for LUXEON 3030 HE and LUXEON 3030 HE Plus 6500K, at 65mA, T<sub>i</sub>=25°C

NOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, O
6500K	Single 3-Step MacAdam ellipse	(0.3123, 0.3282)	0.00669	0.00285	58.57°
6500K	Single 5-Step MacAdam ellipse	(0.3123, 0.3282)	0.01115	0.00475	58.57°

Notes for Table 6g:
1. Lumileds maintains a tolerance of ±0.007 on x and y color coordinates in the CIE 1931 color space.




Figure 9h. color bin structure for LUXEON 3030 HE Plus - NightScape, at 65mA, T<sub>i</sub>=25°C

Table 6h. 3-step MacAdam ellipse color bin definitions for LUXEON 3030 HE Plus - NightScape, at 65mA, T<sub>i</sub>=25°C

N	IOMINAL CCT	COLOR SPACE	CENTER POINT [1] (cx, cy)	MAJOR AXIS, a	MINOR AXIS, b	ELLIPSE ROTATION ANGLE, Θ
	1850	Single 3-Step MacAdam ellipse	(0.5510, 0.4300)	0.0096	0.0046	49.27°

Notes for Table 6h:

# Forward Voltage Bins

Table 7a. Forward voltage bin definitions for L130-xxxxHA30000x1, T<sub>i</sub>=25°C

BIN	FORWARD VOLTAGE [1] (V <sub>f</sub> )		
BIN	MINIMUM	MAXIMUM	
K	2.66	2.76	

Notes for Table 7a:

Table 7b. Forward voltage bin definitions for L130-xxxxHB30000B1, T<sub>i</sub>=25°C

BIN	FORWARD VOLTAGE <sup>[1]</sup> (V <sub>f</sub> )		
BIN	MINIMUM	MAXIMUM	
L	2.75 2.85		

Lumileds maintains a tolerance of  $\pm 0.007$  on x and y color coordinates in the CIE 1931 color space.

<sup>1.</sup> Lumileds maintains a tolerance of  $\pm 0.1V$  on forward voltage measurements.

Notes for Table 7b: 1. Lumileds maintains a tolerance of  $\pm 0.1 V$  on forward voltage measurements.

## **Mechanical Dimensions**




Figure 10. Mechanical dimensions for LUXEON 3030 HE Plus




Figure 11. Mechanical dimensions for LUXEON 3030 HE

- Notes for Figures 10 and 11:
  1. Drawings are not to scale.
  2. All dimensions are in millimeters.
  3. Tolerance: ±0.10mm.

# **Reflow Soldering Guidelines**




Figure 12. Visualization of the acceptable reflow temperature profile as specified in Table 8

Table 8. Reflow profile characteristics for LUXEON 3030 HE and LUXEON 3030 HE Plus

PROFILE FEATURE	LEAD FREE ASSEMBLY
Preheat Minimum Temperature (T <sub>smin</sub> )	150°C
Preheat Maximum Temperature (T <sub>smax</sub> )	200°C
Preheat Time (t <sub>smin</sub> to t <sub>smax</sub> )	60 to 120 seconds
Ramp-Up Rate ( $T_L$ to $T_p$ )	3°C / second maximum
Liquidous Temperature (T <sub>L</sub> )	217°C
Time Maintained Above Temperature $T_L(t_l)$	60 to 150 seconds
Peak / Classification Temperature $(T_p)$	260°C
Time Within 5°C of Actual Peak Temperature (t <sub>p</sub> )	20 to 40 seconds
Ramp-Down Rate (T <sub>p</sub> to T <sub>L</sub> )	6°C / second maximum
Time 25°C to Peak Temperature	8 minutes maximum

#### Notes for Table 8

# JEDEC Moisture Sensitivity

Table 9. Moisture sensitivity levels for LUXEON 3030 HE and LUXEON 3030 HE Plus

LEVEL	FLOOR LIFE		SOAK REQUIREMENTS STANDARD		
LEVEL	TIME	CONDITIONS	TIME	CONDITIONS	
3	168 Hours	30°C / 60% RH	192 Hours +5 / -0	30°C / 60% RH	

<sup>1.</sup> All temperatures refer to the application Printed Circuit Board (PCB), measured on the surface adjacent to the package body.

## Solder Pad Design




Figure 13. Recommended PCB solder pad layout for LUXEON 3030 HE and LUXEON 3030 HE Plus

Notes for Figure 13:

- Drawings are not to scale.
   All dimensions are in millimeters.

# **Packaging Information**

# **Pocket Tape Dimensions**




Figure 14. Pocket tape dimensions for LUXEON 3030 HE and LUXEON 3030 HE Plus

Notes for Figure 14:

- Drawings are not to scale.
   All dimensions are in millimeters.

## **Reel Dimensions**




Figure 15. Reel dimensions for LUXEON 3030 HE and LUXEON 3030 HE Plus

- Notes for Figure 15:
  1. Drawings are not to scale.
  2. All dimensions are in millimeters.

## **About Lumileds**

Companies developing automotive, mobile, IoT and illumination lighting applications need a partner who can collaborate with them to push the boundaries of light. With over 100 years of inventions and industry firsts, Lumileds is a global lighting solutions company that helps customers around the world deliver differentiated solutions to gain and maintain a competitive edge. As the inventor of Xenon technology, a pioneer in halogen lighting and the leader in high performance LEDs, Lumileds builds innovation, quality and reliability into its technology, products and every customer engagement. Together with its customers, Lumileds is making the world better, safer, more beautiful—with light.

To learn more about our lighting solutions, visit lumileds.com.



©2025 Lumileds Holding B.V. All rights reserved. LUXEON is a registered trademark of the Lumileds Holding B.V. in the United States and other countries. lumileds.com

Neither Lumileds Holding B.V. nor its affiliates shall be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding B.V. and/or its affiliates have attempted to provide the most accurate information and data, the materials and services information and data are provided "as is," and neither Lumileds Holding B.V. nor its affiliates warrants or guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. and its affiliates reserve the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data. A listing of Lumileds product/patent coverage may be accessed at lumileds.com/patents.